

# MATERIAL SAFETY DATA SHEET

### DATE OF ISSUE: 9th MAY 2024

# SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Part Number(s): Use: Supplier:

# **BARE-CO THREAD LOCK**

R24S (10ml), R24M (50ml)Anaerobic adhesive.R H Bare Pty LtdABN22 Williamson RoadTel 02Ingleburn NSW 2565Email

ABN 95 000 588 214 Tel 02 9829 7077 Email: enquiries@bareco.com.au

# SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture Hazardous according to the criteria of Safe Work Australia.

### GHS Classification:

Hazard Class	Hazard Category
Skin sensitizer	Category 1
Acute hazards to the aquatic environment	Category 2
Chronic hazards to the aquatic environment	Category 2
Serious eye irritation	Category 2
Hazard pictogram:	
Signal word:	Warning
Hazard statement(s):	H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.
	H319 Causes serious eye irritation.
Precautionary Statement(s)	•
Prevention:	P261 Avoid breathing vapors, mist, or spray.
	P272 Contaminated work clothing should not be allowed out of the workplace.
	P273 Avoid release to the environment.
	P280 Wear protective gloves/eye protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water.
	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
	P362 Take off contaminated clothing.
	P363 Wash contaminated clothing before reuse.
	P391 Collect spillage.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
Diamagala	P337+P313 If eye irritation persists: Get medical advice/attention.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
lassification of material Xi - Irritar	t

# Classification of material Xi - Irritant

## Risk phrases:

R36 Irritating to eyes.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long -term adverse effects in the aquatic environment.

### Safety phrases

S23 Do not breathe vapour.

S25 Avoid contact with eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39 Wear suitable gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well -ventilated areas.

### Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).



# MATERIAL SAFETY DATA SHEET

#### COMPOSITION/INFORMATION ON INCREDIENTS **SECTION 3.**

### **INGREDIENTS:**

COMPOSITION/INF	URMATION UN	INGREDIENIS

CHEMICAL ENTITY	CAS NO.	PROPORTION	
Polyglycol dimethacrylate	[25852-47-5]	60%-65% w/w	
Polyglycol oleate	[9004-96-0]	25%-30% w/w	
Cumene hydroperoxide	[80-15-9]	3%-5% w/w	
Propylene glycol	[57-55-6]	0.1%-1% w/w	
Other ingredients determined not to	be hazardous to 100%		

SECTION 4.	FIRST AID MEASURES
Ingestion:	If swallowed, <b>do not</b> induce vomiting. For advice, contact a Poisons Information Centre (Australia Phone 13 11 26 New Zealand Ph: 0800 764 766 USA www.bare-co.com/msds) or a doctor.
Skin:	Remove contaminated clothing and wash affected areas with plenty of water. If irritation, redness or blistering occurs, seek medical attention.
Eyes:	Hold eyes open and flush with water for at least 15 minutes. If irritation develops, seek medical attention.
Inhalation:	If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor.
Advice to doct	or: Treat symptomatically.
First Aid facilit	<b>ies:</b> Eye wash and normal washroom facilities. A safety shower is recommended.

#### **SECTION 5.** FIRE FIGHTING MEASURES

Suitable extinguishing media: Use foam, dry chemical or carbon dioxide.

Hazards from combustion products: In a fire, it will char. Under fire conditions, it will release carbon monoxide, oxides of sulphurand noxious fumes.

Precautions for fire fighters and special protective equipment: If there is a risk of exposure to products of combustion, fire-fighters should wear self-contained breathing apparatus.

#### **SECTION 6.** ACCIDENTAL RELEASE MEASURES

Wear protective gloves, chemical goggles and safety boots. Wipe up residue with a cloth. For large spills contain and collect with inert absorbent materials (e.g. sand, earth, vermiculite). Transfer to sealable containers suitable for storing spilled material. Flush areas in contact with spilled material with adequate warm soapy water to render the area safe for human contact. Note: Residues are slightly water soluble. Do not contaminate watercourse. Dispose of solid residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

#### HANDLING AND STORAGE SECTION 7.

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE

CONTROLS/PERSONAL PROTECTION. Use in a well ventilated area. Avoid breathing vapour. Storage: Store indoors in a cool, dry and well ventilated area. Keep containers sealed when not in use. Store in original containers away from heat, sparks and open flames. Store at or below 38°C.

#### **SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

National exposure standards: TWA :10 mglm<sup>3</sup> as propylene glycol (particulates)

Engineering controls:

: 474 mglm<sup>3</sup> as propylene glycol (vapour and particulates) None required under normal conditions of use, but if vapour or mist is being generated, use a local mechanical exhaust

**Personal protective equipment:** Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, neoprene or butyl rubber gloves and safety glasses with side shields. Use a well ventilated area. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.



# MATERIAL SAFETY DATA SHEET

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

## Physical data:

Appearance: Specific gravity: Solubility: Flash point (PMCC): VOC content: Blue Liquid 1.1 @ 24°C Slightly soluble in water > 90°C 49.3 g/l

### SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Open flames, sparks, strong heat.

**Incompatible materials:** Keep away from strong oxidising agents, acids and alkalies. This product is destabilised by strong reducing agents.

Hazardous decomposition products: In a fire, it can release carbon monoxide, oxides of sulphur and noxious fumes.

Hazardous reactions: Hazardous polymerisation will not occur.

## SECTION 11. TOXICOLOGICAL INFORMATION

### HEALTH EFFECTS:

Acute: Ingestion:	If swallowed, may cause gastrointestinal irritation.
Skin:	Irritating to skin. May cause sensitisation by skin contact.
Eyes:	Contact with the eyes can cause severe irritation.
Inhalation:	Inhalation of vapours may cause respiratory irritation.
Chronic:	Repeated or prolonged skin contact may cause chronic dermatitis.
Toxicity information:	None available for this product.

### SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate waterways or soil. This product may be harmful to aquatic organisms.

# SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of this material should be undertaken by a registered chemical disposal company. Empty containers should be disposed of according to local regulations.

# SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).



## **SECTION 15. REGULATORY INFORMATION**

SUSDP POISON SCHEDULE: None allocated

## **SECTION 16. OTHER INFORMATION**

### Abbreviations/acronyms:

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

### DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by R H Bare Pty Ltd.