

MATERIAL SAFETY DATA SHEET

DATE OF ISSUE: 9th MAY 2024

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Part Number(s): Use: Supplier:

BARE-CO THREAD LOCK

R27M (50ml) Anaerobic adhesive. R H Bare Pty Ltd 22 Williamson Road Ingleburn NSW 2565

ABN 95 000 588 214 Tel 02 9829 7077 Email: enquiries@bareco.com.au

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture Hazardous according to the criteria of Safe Work Australia.

GHS Classification:				
Hazard Class	Hazard Category	<u>Target organ</u>		
Serious eye irritation Target Organ Systemic Toxica	Category 2A	reaspiratory tract irritation		
Single exposure	Hit Category 5	respiratory tract irritation		
Skin sensitizer	Category 1			
Skin irritation	Category 2			
Hazard pictogram:				
Signal word:	Warning			
Hazard statement(s):	H319 Causes serious eye irritation.			
	H315 Causes skin irritation.			
	H317 May cause an allergic skin reaction.			
	H335 May cause respiratory irritation.			
Precautionary Statement(s): Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.				
Trevention.	P264 Wash hands thoroughly after handling.	spray.		
	P271 Use only outdoors or in a well -ventilated are	a.		
	P272 Contaminated work clothing should not be all	owed out of the workplace.		
	P280 Wear eye protection/face protection.			
Response:	P302+P352 IF ON SKIN: Wash with plenty of soap			
	P304+P340+P312 IF INHALED: Remove victim to			
	comfortable for breathing. Call a POISON CENTER P305+P351+P338 IF IN EYES: Rinse cautiously wi			
	contact lenses, if present and easy to do. Continue			
	P333+P313 If skin irritation or rash occurs: Get med			
	P337+P313 If eye irritation persists: Get medical ac	lvice/attention.		
	P362 Take off contaminated clothing.			
	P363 Wash contaminated clothing before reuse .			
Storage:	P403+P233 Store in a well -ventilated place. Keep P405 Store locked up.	container tightly closed.		
Disposal:	P501 Dispose of contents/container to an appropria accordance with applicable laws and regulations.	te treatment and disposal facility in		

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

SECTION 3. COMPOSITION/I	NFORMATION ON INGR	EDIENTS
INGREDIENTS:		
CHEMICAL ENTITY	CAS NO.	PROPORTION
Polyglycol dimethacrylate	[25852-47-5]	>60% w/w
Modified silica dioxide	[68855-54-9]	10-15% w/w
Bisphenol A fumarate	[39382-25-7]	10%-20% w/w
Cumene hydroperoxide	[80-15-9]	1%-<3% w/w
Other ingredients determined not	to be hazardous to 100%	



MATERIAL SAFETY DATA SHEET

SECTION 4. FIRST AID MEASURES

Ingestion:	If swallowed, do not induce vomiting. For advice, contact a Poisons Information Centre (Australia Phone 13 11 26 New Zealand Ph: 0800 764 766 USA www.bare-co.com/msds) or a doctor.
Skin:	Remove contaminated clothing and wash affected areas with plenty of water. If irritation, redness or blistering occurs, seek medical attention.
Eyes:	Hold eyes open and flush with water for at least 15 minutes. If irritation develops, seek medical attention.
Inhalation:	If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor.
Advice to doctor:	Treat symptomatically.
First Aid facilities:	Eye wash and normal washroom facilities. A safety shower is recommended.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Use foam, dry chemical or carbon dioxide.

Hazards from combustion products: In a fire, it will char. Under fire conditions, it will release carbon monoxide, oxides of sulphurand noxious fumes.

Precautions for fire fighters and special protective equipment: If there is a risk of exposure to products of combustion, fire-fighters should wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Wear protective gloves, chemical goggles and safety boots. Wipe up residue with a cloth. For large spills contain and collect with inert absorbent materials (e.g. sand, earth, vermiculite). Transfer to sealable containers suitable for storing spilled material. Flush areas in contact with spilled material with adequate warm soapy water to render the area safe for human contact. Note: Residues are slightly water soluble. Do not contaminate watercourse. Dispose of solid residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Use in a well ventilated area. Avoid breathing vapour.

Storage: Store indoors in a cool, dry and well ventilated area. Keep containers sealed when not in use. Store in original containers away from heat, sparks and open flames. Store at or below 38°C.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards:TWA:10 mglm³ as propylene glycol (particulates): 474 mglm³ as propylene glycol (vapour and particulates)Engineering controls:None required under normal conditions of use, but if vapour or mis

None required under normal conditions of use, but if vapour or mist is being generated, use a local mechanical exhaust

Personal protective equipment: Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, neoprene or butyl rubber gloves and safety glasses with side shields. Use a well ventilated area. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.



MATERIAL SAFETY DATA SHEET

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance: Specific gravity: Solubility: Flash point (PMCC): VOC content: Red Liquid 1.1 @ 24°C Slightly soluble in water > 90°C 49.3 g/l

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Open flames, sparks, strong heat.

Incompatible materials: Keep away from strong oxidising agents, acids and alkalies. This product is destabilised by strong reducing agents.

Hazardous decomposition products: In a fire, it can release carbon monoxide, oxides of sulphur and noxious fumes.

Hazardous reactions: Hazardous polymerisation will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Acute: Ingestion:	If swallowed, may cause gastrointestinal irritation.
Skin:	Irritating to skin. May cause sensitisation by skin contact.
Eyes:	Contact with the eyes can cause severe irritation.
Inhalation:	Inhalation of vapours may cause respiratory irritation.
Chronic:	Repeated or prolonged skin contact may cause chronic dermatitis.
Toxicity information:	None available for this product.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate waterways or soil. This product may be harmful to aquatic organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of this material should be undertaken by a registered chemical disposal company. Empty containers should be disposed of according to local regulations.

SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).



SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by R H Bare Pty Ltd.